



INSTALLATION INSTRUCTIONS



'09-'13 Dodge Ram 1500 3.6L

PART NO. 15248

BILL OF MATERIALS:



- 1. MUFFLER ASSEMBLY
- 2. TAIL PIPE ASSEMBLY



WEAR SAFETY GLASSES



READ INSTRUCTIONS THOROUGHLY BEFORE INSTALLING PRODUCT

SHOP SUPPLIES:



SPRAY LUBRICANT

To ease removal of existing exhaust components (especially on older vehicles) spray penetrating lubricant on all fasteners and hangers/insulators that will be loosened or removed and let soak before disassembly.

HARDWARE KIT:

- 1. [2] 3.00" Clamps

MINIMUM REQUIRED TOOLS:



Pry Bar



15mm Socket


MAGNAFLOW RECOMMENDS PROFESSIONAL INSTALLATION ON ALL THEIR PRODUCTS



WARNING: When working on, under, or around any vehicle exercise caution. Please allow the vehicle's exhaust system to cool before removal, as exhaust system temperatures may cause severe burns. If working without a lift always consult vehicle manual for correct lifting specifications. Always wear safety glasses and ensure a safe work area. Serious injury or death could occur if safety measures are not followed.

ATTENTION: Always install any supplied band or U-bolt clamps to the proper torque specifications of 40-45 ft-lbs for band clamps and 30-35 ft-lbs for U-bolt clamps. Over tightening will result in the clamp breaking and will NOT be warranted by MagnaFlow.


INSTALLATION INSTRUCTIONS




Step 1. Begin removing the OEM exhaust by unbolting the muffer assembly rearward of the flange coupling.



Step 2. Next unbolt the OEM clamp attaching the tail pipe assembly to the muffer assembly. Remove the welded hangers from the rubber insulators using a pry bar. Do not discard or damage the insulators as they will be needed to install your new system. The OEM system may now be removed.



Step 3. You are now ready to install your new MAGNAFLOW system. Loosely attach the the Muffer Assembly to the OEM pipe outlet using the supplied 3.00" clamp. Engage the welded hanger to the OEM rubber insulator. Leave all clamps and hardware loose for final adjustment of the complete system.



Step 4. Slip the inlet of the Tail Pipe Assembly over the outlet of the Muffer Pipe Assembly and loosely secure using the supplied 3.00" clamp and 15mm socket. Engage all welded hangers to the OEM rubber insulators.



Step 5. Once a final position has been chosen for the new system, evenly tighten all fasteners from front to rear using the torque specifications on page one of this document. Inspect all fasteners after 25-50 miles of operation and retighten if necessary.